

C2800SIR22-13M



High definition , image quality is equivalent to 720P IP camera

Low illumination , 0.01Lux @ (F1.2,AGC ON),0 LUX with IR

Support auto Day/Night function

With P2P [coaxial transmission](#) , no any delay

Using coaxial cable 75-3(or above) ,The transmission distance can up to 500M

Switch mode for HD 960P and normal 960H

P/N two- in -One , easy to switch

Perfect match with AHD DVR



Parameters	1.3 MP IR Dome Camera
Camera	
Sensor	1/3 Sony IMX238 sensor
Signal system	PAL/NTSC
Horizontal Resolution:	Resolution can up to 960P IP camera
Min illumination	Color :0.1Lux @(F1.2,AGC ON),0 LUX with IR B/W :0.01 Lux @ (F1.2,AGC ON),0 LUX with IR
Shutter time	1/50(1/60)S to 1/100,000 S
Lens	Professional HD lens 3.6mm F1.2
Lens mount	M12
Day/Night	IR Cut Filter Auto Switch
Sync mode	Internal Synchronization
S/N Ratio	>58dB

General range	
Working Temperature/Humid	-10°C~60°C Humidity 90% or less (non-condensing)
Power Supply	DC12V±10%
Power Consumption	"IR2": 5W MAX;
Rating:	IP65
IR Range	"IR2":15-25 M;
Dimensions (mm)	Φ124mm*92mm
weight	267g